



## TECHNICAL DATA

### FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1565919

<b>Dimensions:</b>	<b>Height:</b>	26"
	<b>Outside Diameter:</b>	12.75"
	<b>Inside Diameter:</b>	8.375"
<b>Top End Cap:</b>	<b>Material:</b>	Electro Galvanized (22 ga)
	<b>Style:</b>	Open, 15" x 16.50" flange
<b>Bottom End cap:</b>	<b>Material:</b>	Electro Galvanized (22 ga)
	<b>Style:</b>	Closed
<b>Gasket:</b>	5/8" x 5/8" x 10.75" ID isoprene sponge applied on top cap	
<b>Inner Retainer:</b>	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
<b>Outer Retainer:</b>	3 Woven bands	
<b>Filter Media Area:</b>	75 ft <sup>2</sup>	
<b>Pleat Count:</b>	111	
<b>Media Type:</b>	100% Spun-bond Polyester	
<b>Permeability:</b>	20 cfm/ft <sup>2</sup> @ 0.5" w.g.	
<b>Maximum Temperature:</b>	180° F	

### PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

<b>PARTICLE SIZE:</b>	0.5 micron-----	99.7%
	1.0 micron-----	99.8%
	2.0 micron-----	100 %