



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1566228

| | | |
|-----------------------------|--|----------------------------|
| Dimensions: | Height: | 11.5" |
| | Outside Diameter: | 16" |
| | Inside Diameter: | 9.63" |
| Top End Cap: | Material: | Electro Galvanized (22 ga) |
| | Style: | Open |
| Bottom End cap: | Material: | Electro Galvanized (22 ga) |
| | Style: | Open |
| Gasket: | 1/2" x 1/2" x 14" Neoprene attached to one end 1/2" x 1/2" x 12" Neoprene attached to one end | |
| Inner Retainer: | Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area | |
| Outer Retainer: | 1 woven band | |
| Filter Media Area: | 47 ft ² | |
| Pleat Count: | 137 | |
| Media Type: | 100% Spun-bond Polyester | |
| Permeability: | 20 cfm/ft ² @ 0.5" w.g. | |
| Maximum Temperature: | 180° F | |

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

| | | |
|-----------------------|-----------------|-------|
| PARTICLE SIZE: | 0.5 micron----- | 99.7% |
| | 1.0 micron----- | 99.8% |
| | 2.0 micron----- | 100 % |