



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1566716

| | | |
|-----------------------------|--|-----------------------------|
| Dimensions: | Height: | 26" |
| | Outside Diameter: | 12.75" |
| | Inside Diameter: | 8.375" |
| Top End Cap: | Material: | 304 Stainless Steel (24 ga) |
| | Style: | Open |
| Bottom End cap: | Material: | 304 Stainless Steel (24 ga) |
| | Style: | Closed |
| | Bolt Hole: | .540" |
| Gasket: | 1/2" x 1/2" x 10.25" ID isoprene sponge applied on top cap | |
| Inner Retainer: | Stainless steel expanded metal 3/8" x 5/8" 72% open area | |
| Outer Retainer: | 2 Nylon bands | |
| Filter Media Area: | 170 ft ² | |
| Pleat Count: | 314 | |
| Media Type: | Cellulose/Polyester Blend | |
| Permeability: | 14 cfm/ft ² @ 0.5" w.g. 112 L/sec/m ² @ ΔP 20 mm w.g. | |
| Maximum Temperature: | 180° F | |

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

| | | |
|-----------------------|-----------------|-------|
| PARTICLE SIZE: | 0.5 micron----- | 99.8% |
| | 1.0 micron----- | 99.9% |
| | 2.0 micron----- | 100 % |