



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1566801

Dimensions:	Height:	22.3"
	Outside Diameter:	9.23", 5/8" lip flange
	Inside Diameter:	5.837"
Top End Cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open
Bottom End cap:	Material:	Electro Galvanized (22 ga)
	Style:	Closed, with 5/8" lip flange
	Bolt Hole:	0.94"
Gasket:	3/8" x 1/2" x 8.156" ID isoprene sponge applied on top cap	
	3/8" x 1/2" x 9.312" ID isoprene sponge applied on bottom cap, under lip flange toward filter body	
Inner Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	1 Woven Band	
Filter Media Area:	43 ft²	
Pleat Count:	97	
Media Type:	100% Spun bond Polyester	
Permeability:	20 cfm/ft² @ 0.5" w.g.	
	160 L/sec/m² @ ΔP 20	
Maximum Temperature:	180° F (82.22° C)	

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

PARTICLE SIZE:	0.5 micron-----	99.7%
	1.0 micron-----	99.9%
	2.0 micron-----	100 %