

TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1567942

Dimensions:	Height: Outside Diameter: Inside Diameter:	54.25" 6.85" 3.60"		
Top End Cap:	Material: Style:	Electro Galvanized (22 ga) Open with 8.125" x 8.125" Flange and holes drilled in each corner		
Bottom End cap:	Material: Style:	Electro Galvanized (22 ga) Closed		
Gasket:	1/2" x 5/8" x 6.875" II cap	1/2" x 5/8" x 6.875" ID D-Style applied under open cap		
Inner Retainer:		Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area with Ground Wire		
Outer Retainer:	5 Woven bands	5 Woven bands		
Filter Media Area:	110 ft ²	110 ft ²		
Pleat Count:	87	87		
Media Type:	100% Spun-bond Pol	100% Spun-bond Polyester, Aluminized		
Permeability:	26 cfm/ft² @ 0.5" w.	26 cfm/ft² @ 0.5" w.g.		
Maximum Temperature:	180° F	180° F		

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

PARTICLE SIZE:	0.5 micron	99.7%
	1.0 micron	99.8%
	2.0 micron	100 %