

SELECTING THE RIGHT DUST CARTRIDGE FILTER

[LEARN MORE](#)




ENGINEERING YOUR SUCCESS.

At Parker Hannifin, when it comes to dust cartridge filters, we're known for delivering products that provide higher efficiencies with cleaner air, longer filter life and greater energy savings. We are at the forefront of technology and innovation; we develop and manufacture proprietary filter media technologies using our advanced research capabilities to ensure the latest developments are in our filters.



ENGINEERING **YOUR** SUCCESS.



Our products are performance certified by 3rd party testing services, and our customers can trust our products will perform reliably. Everything we do is guided by the following principles:

- **Customer Focus** – Providing excellent products and services that meet our customer needs.
- **Integrity and Compliance** – Strict adherence to all statutory, regulatory, and customer requirements.
- **Quality Management System** – Defining our expectations of safety, quality, reliability and service; with a drive for continual improvement of all processes using industry expertise and customer feedback.
- **Engagement** – Employees and suppliers engaged and committed to improving quality performance and creating a competitive advantage for both Parker Hannifin and our Customers.

We continue to build on our strong foundation of quality, elevating our standards to the next level. That's what we've become known for. That's our cartridge filter business. That's Parker Hannifin.




ENGINEERING **YOUR** SUCCESS.

Application and operating conditions are important considerations. Temperature, moisture in the gas stream, presence of oils, spark carryover, FDA compliance and the abrasive nature of the particulates are all factors that need to be considered.

MERV ratings allow us to understand the clean, fractional efficiency of a filter. MERV ratings are assessed on a scale between 1 and 16. The higher the ratings, the more effective a filter is at capturing smaller airborne particulates.

For example, filters with a MERV rating of four or lower are usually good in an application for capturing things like, pollen, dust mites and spray paint dust, while a filter with a MERV rating of 13 or higher is good for things like bacteria and smoke.

Pressure and pressure loss (sometimes called pressure drop) is the resistance to airflow that is created by the cartridge filter and dustcake. If the filter has a higher pressure drop, the filtration system will require more energy to move air through the filter. Pressure is impacted by not only the filter and filter media, but also by the dust collected.



Load is how the particulates are collected within the filter, specifically on the filter media. There are two types of filtration methods, surface and depth.

Depth loading allows for the dust to be captured deep into the pores of the filter. This creates higher pressure loss and higher energy usage from the filtration system because portions of the filter media become blinded over time lowering the overall air permeability.

Surface filtration has a barrier on the surface that allows for the dust particles to be captured on top instead of in the voids of the media. Surface loading allows for longer filter life, lower pressure drop and lower energy consumption over the life of the filters.

Generally speaking, surface filtration has a higher filtration efficiency rating than depth loading due to the smaller pore size of the media.

When media is properly applied it can minimize energy consumption and compressed air usage, while creating maximum lifespan for the cartridge filter.

It's helpful to think about filter media in a layered approach. There is a base layer of media which is often sufficient for a variety of applications. From that base, a range of treatments can be added to the media fibers or to the surface to modify the filter performance. For example, treatments like fire retardant finishes are often added for environments with the potential for spark carryover. An oleophobic treatment will discourage media fouling due to oil residue in the gas stream. A fine filtration layer can be added such as nanofibers or ePTFE membrane to remove very fine particulate from the gas stream.



ENGINEERING **YOUR** SUCCESS.

Cellulose and Cellulose Blends

Cellulose (or paper) typically have a lower MERV rating and not good for applications with fine or abrasive particulate or moisture. Cellulose can be good for applications that include weld fume, cement dust, lead dust and milled flour.

Average MERV rating of 10 for the base media. MERV rating of 15 with nanofibers applied to the surface of the base media.

***Temperature rating
200F continuous.***

Spunbond Polyester

Spunbond polyester is a synthetic media. It has similar filtration efficiencies to cellulose. It's strong, more resistant to abrasion, as well as moisture. It also has a better life cycle. It's good in applications such as chemical processing, industrial, pharmaceutical, and food.

Average MERV rating of 10. MERV rating of 15 with nanofibers applied to the surface. MERV rating of 16+ with ePTFE membrane applied to the surface of the base media.

***Temperature rating
265F continuous.***

PPS

PPS media is used in environments and applications with high acidity content. It's used in applications such as dryers and glass furnaces.

Average MERV rating of 10 for the base media. MERV rating of 16+ with ePTFE membrane applied to the surface of the base media.

***Temperature rating
350F continuous.***

Aramid

Aramid offers better options for operating conditions in higher heat as well as applications like cement, gypsum, smelting and certain chemical applications.

Average MERV rating of 10. MERV rating of 16+ with ePTFE membrane applied to the surface of the base media.

***Temperature rating
375F continuous.***

Polyester Anti-static

Combustible dust. That's what you should think about when you think about anti-static filter media. Anti-static media keeps collected dust discharged, so it can be safely released when needed. Anti-static media is especially useful in environments where an application requires grounding.

***Average MERV rating of 10 for the base media. MERV rating of 16+ with ePTFE membrane applied to the surface of the base media. Temperature rating
275F continuous.***

Polypropylene

Polypropylene media is typically good with high levels of particulates and the presence of moisture. It offers a longer filter life, especially when compared to cellulose and cellulose blends. It's good in applications that include food, metals, resins and fine chemicals.

Average MERV rating of 10 for the base media. MERV 16+ with ePTFE membrane applied to the surface of the base media.

***Temperature rating
170F continuous.***

NANOFIBER TECHNOLOGY

Nanofibers are very small fibers approximately 200 nanometers in diameter deposited on the surface of the base media layer to reduce the pore size and improve the collection efficiency. A typical rating for a media with nanofibers is MERV 15 which means that it is greater than 85% efficient at capturing particulate in the 0.3 to 1.0 micron range on clean fabric, meaning media or fabric without a dustcake.



Nanofiber filtration
technology at 5000x



EXPANDED PTFE MEMBRANE (ePTFE)

PTFE fine powder is processed into a tape that is stretched and laminated to the base media. The result is an average pore size of approximately 0.5 micron and a typical rating of MERV 16+ which means that it is greater than 95% efficient at capturing particulate in the 0.3 to 1.0 micron range. This rating signifies that ePTFE membranes are capable of reaching much higher filtration efficiencies such as HEPA ratings.

ENGINEERING **YOUR** SUCCESS.

Selecting the Right Cartridge Filter

Consider these factors to help you choose the best cartridge filter for your industrial process

Part Number	Material	MERV Rating	General Usage*	Finish Type	Typical Applications
PR017	Protura Paper	15	For most applications		Abrasive blasting, carbon black, powder paints, dry chemical processing, pharmaceuticals etc.
PR018	Protura Paper	15	For applications where live sparks could enter the dust collector. Will not suppress fires if collected materials are combustible.	Fire Retardant	Welding flame cutting, plasma cutting, laser cutting, metal spraying, ferrous metal grinding, etc.
PR019	Protura Paper	15	Contact Product Specialist team for assistance		Contact Product Specialist team for assistance
PR010	Paper	10	Works well with most applications. Finish adds moisture resistance to the media.	Hydrophobic	Abrasive blasting, carbon black, powder paints, dry chemical processing, pharmaceuticals etc.
PR011	Paper	10	For applications where live sparks could enter the dust collector. Will not suppress fires if dust collected is combustible.	Fire Retardant	Welding flame cutting, plasma cutting, laser cutting, metal spraying, ferrous metal grinding, etc.
PR020	Paper	10	For applications where static dissipation is required. (Not to be used for odor control)	Carbon Impregnated	Various applications. Contact Product Specialist team for assistance
PE825	Polyester	10	For applications where static dissipation is required. (Not to be used for odor control)		Grain, plastics, chemical processing. Contact Product Specialist team for assistance
PE806	Polyester	10	For applications where high strength media and excellent release characteristics are required		Cardboard, cement, cocoa, coffee, paper, rubber grinding, powder coating, polishing, etc.

Selecting the Right Cartridge Filter

Consider these factors to help you choose the best cartridge filter for your industrial process

Part Number	Material	MERV Rating	General Usage*	Finish Type	Typical Applications
PE922	Polyester	10	For applications where high strength media and excellent release characteristics are required	Oleophobic	Composite grinding, textiles, tobacco
PE1013	Polyester	10	For applications where live sparks could enter the dust collector. Will not suppress fires if collected materials are combustible	Fire Retardant	Electric arc furnace applications. Other metal fume applications. Grinding, cutting, etc.
PE1017	100% Polyester Non-Woven with Nanofiber Fine Filtration Layer	15	For applications requiring more efficient capture of sub-micron particles, 85% efficient at removing particulate in the 0.3 – 1.0 micron range		LEARN MORE
QP806	Preveil Polyester	16+	For applications demanding extremely high filtration efficiencies or difficult dust cake release requirements		Food, asbestos, pesticides, fluidized bed dryers, agglomerating materials
QP825	Preveil Polyester	16+	For applications where static dissipation is required and a fine filtration layer is needed		Grain, plastics, chemical processing, etc. Please contact Product Specialist team for assistance
NX821	Aramid	10	For applications with high extreme temperatures		Cement Mills, Paint, Pigments, Coal, Gypsum, Coal-Fired Boiler Fly Ash Receivers, Dryers, General Process
QN821	Preveil Aramid	16+	For applications with High Extreme temperatures with applications demanding high filtration efficiencies or difficult cake release		Cement Mills, Paint, Pigments, Coal, Gypsum, Coal-Fired Boiler Fly Ash Receivers, Dryers, General Process

Selecting the Right Cartridge Filter

Consider these factors to help you choose the best cartridge filter for your industrial process

Part Number	Material	MERV Rating	General Usage*	Finish Type	Typical Applications
RY811	PPS	10	For applications with High Extreme temperatures with applications demanding high filtration efficiencies or difficult cake release.		Cement Mills, Paint, Pigments, Coal, Gypsum, Coal-Fired Boiler Fly Ash Receivers, Dryers General Process
QR811	Preveil PPS	16+	For applications with extreme temps demanding high filtration efficiency or difficult cake release. Possible acid gas stream. Caution on oxygen levels		Cement, Paint, Pigments, Coal-Fired Boilers, Dryers, Catalyst Manufacturing, Waste-to-Energy
PP794	Polypropylene	10	For low temp applications where moisture is present		General process industries including food, pharmaceuticals, dryers
QL794	Preveil Polypropylene	16+	For low temp applications - moisture is present and a fine filtration layer is needed or dustcake release is needed		General process industries including food, pharmaceuticals, dryers

PROTURA SB NANO

BHA® Protura® SB Outperforms Conventional Spunbond Polyester

We are at the forefront of technology and innovation; we develop and manufacture proprietary filter media technologies using our advanced research capabilities to ensure the latest developments are in our filters. ProTura SB, the most advanced nanofiber filtration technology is available in our pleated cartridge filter elements for use in most cartridge style dust collectors. ProTura SB is a 100% synthetic base media with a proprietary nanofiber layer applied to the collection surface that's ready to take on the most demanding applications.

ProTura SB advanced nanofiber filtration technology is proven to achieve


- Higher efficiency and greater energy savings than any other standard cartridge filter media
- Cleaner air
- Longer filter life
- Greater resistance to moisture in the air stream
- Superior durability compared to standard 80/20 media (cellulose/polyester blend) media

Higher Efficiency and More Energy Savings.

Surface loading is the key, ProTura SB advanced nanofiber filters feature an advanced nanofiber layer of synthetic fibers so extremely fine; they are measured in fractions of a micron (nanometers). This ultra-thin layer traps dust on the surface of the filter before it can embed deeper in the media – leading to better cleaning efficiency with fewer pulses and significantly less compressed air use.

Cleaner Air.

Our ProTura SB advanced nanofiber filters are more efficient in capturing sub-micron particles than conventional cartridge media options. Conventional cartridge filters are not capable of capturing such small particles and often require the additional use of a costly HEPA filter to ensure a safe breathing environment.



Nanofiber filtration
technology at 5000x

Protura® SB Nano

[SEE THE VIDEO](#)

THIS IS SUPERIOR

***You need a dust
collection filter***

*Parker manufactures filters for many OEM dust collectors
We design improvements to help your bottom line
We manufacture our filter media*

Contact us today and we can cross-reference your part number.

Discover the difference in performance and value with our OEM replacement filters. We design filters to meet special applications or as an aftermarket replacement filter for other brand OEM dust collectors. We engineer and manufacture the right filter for your needs and to solve problems you may have experienced with the OEM brand filter. **Parker.com/OEMfilters**



We manufacture  placement filters
for most OEM collectors

SEE THE VIDEO

The beauty of Parker cartridge filters is the level of customization available. If a customer or prospect has a specific need that is not a current part of the cartridge filter offering, we can always offer a custom solution when it comes to media.

When it comes to cartridge filters, it's about;

- MERV ratings and which is appropriate for which application
- Air permeability and pressure drop
- Filtration method, depth loading and surface loading
- Operating Conditions, such as temperature, moisture, condensation and abrasion
- Media – cellulose, cellulose blend, Aramid, spun bond polyester, PPS, or custom

When those things come together, we achieve higher efficiencies for our customers with cleaner air, longer filter life and greater energy savings.

That's what we've become known for. That's our cartridge filter business. **That's Parker Hannifin.**

Parker Hannifin Corporation
Industrial Gas Filtration and Generation Division
11501 Outlook Street, Suite 100
Overland Park, KS 66211 USA
p: 800.821.2222 | f: 816.353.1873
www.BHA.com



© 2022 Parker Hannifin Corporation

Industrial Applications

- Abrasive Blasting
- Batch Mixing
- Blending
- Buffing
- Bulk Powder Handling
- Carbon Black
- Cast Iron
- Drilling
- Dry Chemicals
- Filling
- Finishing
- Grinding
- Material Handling
- Metal Working
- Packaging
- Paint Pigment
- Paper Dust
- Polishing
- Powder Coating
- Sanding
- Sawing
- Screening
- Smelting
- Spices
- Weighing
- Welding
- Wood Dust

ENGINEERING **YOUR** SUCCESS.